



**Specifications Philips LED Panel Coreline RC132V 33W 3600lm - 840 Cool White | 60x60cm - UGR <19 - Dali Dimmable - Emergency 3H**

[View Product](#)

## General Information

|                          |   |
|--------------------------|---|
| SKU                      | 238217                                  |
| EAN                      | 8718699967109                           |
| Brand                    | Philips                                 |
| Manufacturer Name        | RC132V G4 LED36S/840 PSD W60L60 OC ELB3 |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 50000                                   |
| Series                   | RC132V                                  |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 33                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3600               |

|                          |                           |
|--------------------------|---------------------------|
| Luminous Efficacy (lm/W) | 123                       |
| IP-rating                | IP44                      |
| Impact Protection (IK)   | IK03 - 0.35 joule         |
| Fixture Connection       | Push-in-connector, 6-pole |
| Driver Included          | Yes                       |
| Power factor             | >0.90                     |
| Product Type Category    | LED Panel                 |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | 3H Emergency Light             |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 16      |

[Sensor Information](#) [Discover the largest lighting specialist in Europe](#) [Customised quotation](#)

Type of sensor



Up to 7 years warranty

No Sensor

⤵ Easy return process

